



# Bowers & Wilkins

**703 S3**

Technical Information



#### Technical features

Decoupled Carbon Dome tweeter  
Solid Body Tweeter-on-Top  
Continuum™ cone FST™ midrange  
Decoupled midrange  
Aerofoil™ Profile bass cones  
Flowport™

#### Description

3-way vented-box system

#### Drive units

1x ø25mm (1in) Decoupled Carbon Dome high-frequency  
1x ø150mm (6in) Continuum cone FST midrange  
2x ø165mm (6.5in) Aerofoil profile bass

#### Frequency range

30Hz to 33kHz

#### Frequency response

(+/-3dB from reference axis)

46Hz - 28kHz

#### Sensitivity

(on axis at 2.83Vrms at 1m)

90dB

#### Harmonic distortion

2nd and 3rd harmonics (90dB, 1m on axis)  
<1% 90Hz - 22kHz  
<0.5% 120Hz - 20kHz

#### Nominal impedance

8Ω (minimum 3.1Ω)

#### Recommended amplifier power

30W - 200W into 8Ω on unclipped programme

#### Max. recommended cable impedance

0.1Ω

#### Dimensions

Height: 1010mm (39.8in) cabinet only  
1117mm (44in) including tweeter and plinth

Width: 192mm (7.6in) cabinet only  
290mm (11.4in) including plinth

Depth: 316mm (12.4in) cabinet only  
353mm (13.9in) including grille and terminals  
372mm (14.6in) including plinth

#### Net weight

28.8kg (63.5lbs)

#### Finishes

Cabinet: Gloss black  
Satin white  
Mocha  
Rosenut (APAC only)

Grille: Black  
Grey (Satin White only)